


Product Data Sheet TECHNICAL SPECIFICATIONS

Series	
Description	<ul style="list-style-type: none"> • Engineered pre-finished plank (G9) flooring • Sawn wear layers (not rotary) • 4 sides tongue and groove and micro-bevel
Overall Thickness	13/32" (10.5mm)
Top Wear Layer	1/12" (2mm)
Lower Substrate	3/8" (9mm) pine 5 ply
Width	G9: 3 9/16" (90mm)
Length	G9 : 1.5 to 4 feet (450mm ~ 1200mm) randomly nested in each box average length ranges from 28" to 34"
Wood Species Available - Select & Better Grade	<ul style="list-style-type: none"> • American Red Oak • American Walnut, Cherry & Hard Maple • Brazilian Walnut (Ipe) & Brazilian Cherry (Jatoba)
Wood Species Available - Country Grade	<ul style="list-style-type: none"> • Hickory • Australian Cypress and Wormy Chestnut
Finish	Aluminum Oxide UV cured multilayer coating
Finish Gloss	40% standard
Finish Hardness	6H ± 1H
Abrasive Resistance	CS-10: 1000 rpm average weight loss 0.0286 g
	CS-17: 14,500 revolutions to finish wear through
Moisture Resistance	All glue lines rated Marine Grade, Exterior WBP
Formaldehyde	E1 European ultra-low emission rated
Installation	Glue down, Staple down, or Floated
	Above, On and Below Grade
Quantity / Box	one box = 36.62 SF
Quantity / Pallet	one pallet = 56 Boxes = 2050.72 SF
Warranty	<ul style="list-style-type: none"> • 25 years residential wear through limited warranty • 1 year light commercial warranty • Lifetime Structure warranty